VETERINARY EQUIPMENT SET SERVICE FIELD

Support and Consumables
Handbook
6545-01-508-6972
UA 4901
LIN M30340

REVISED

April 2007 U.S. Army Medical Materiel Agency The information contained in this manual was prepared by the U.S. Army Medical Materiel Agency, Materiel Acquisition Directorate, Ancillary Care Division, Fort Detrick, MD

This manual is still in draft form and may contain inaccuracies. To report inaccuracies or additions, please contact 301-619-4301/4316, DSN 343-4301/4316, or at USAMMACRM@amedd.army.mil Responses may also be mailed to:

Commander U.S. Army Medical Materiel Agency MCMR-MM0-AC 1423 Sultan Drive, Suite 100 Fort Detrick, MD 21702-5001

NOTE: CLICK ON TITLE FOR DIRECT LINK

TABLE OF CONTENTS

SECTION			PAGE
<u>NO.</u>	<u>DEVICE</u>	<u>NSN</u>	<u>NO.</u>
1	ANESTHESIA MACHINE PORTABLE COMPACT	(J) 6515-01-503-5331	1
2	CONCENTRATOR OXYGEN 1-5 LPM	(J) 6515-01-434-4629	7
3	LIGHT HEAD GENERAL PURPOSE	(J) 6230-01-520-3474	11
4	LIGHT SURGICAL STAND	(J) 6530-01-518-9854	15
5	OTOSCOPE & OPHTHALMOSCOPE SET	(J) 6515-01-333-3165	19
6	REFRIGERATOR BLOOD COOLING & STORAGE		
	FIELD	(J) 4110-01-506-0895	23
7	SINK UNIT SURGICAL SCRUB AND UTENSIL	(J) 6530-01-429-6715	27
8	STERILIZER SURGICAL INSTRUMENT STEAM	(J) 6530-01-531-4807	29
9	ULTRASOUND SYSTEM PORTABLE	(J) 6525-01-503-7182	33

ANESTHESIA MACHINE PORTABLE COMPACT TOC

OCEANIC MEDICAL PRODUCTS INC MODEL #: 2200

Manufacturer's PHONE: (913) 874-2000 FAX: (913) 874-2005

Website: http://www.oceanicmedical.com

AAC "J" ITEM NSN 6515-01-503-5331

UA's: 4901

USAMMA POC: Materiel Acquisition Directorate, 301-619-7403, DSN 343-7403 UNIT PRICE: \$22,805.00

System Description: The Magellan-2200 Anesthesia Machine is compact, robust and flexible, easy to move and was designed for military field hospitals, general civilian hospitals, office-based anesthesia and surgery centers of every description. It is pneumatically powered and contains an electronic ventilation monitor that is A/C or battery powered. The Magellan-2200 may be mounted on a tabletop or on a mobile cart. The unit is designed as a simple to operate unit containing all of the modes and necessary components to deliver a basic anesthetic, including a mechanical ventilator and a single agent vaporizer. All of the safety systems required are employed onboard and easy to utilize.

Tests performed: All Anesthesia cases with a single agent vaporizer.



Magellan 2200 Portable Anesthesia Machine NSN 6515-01-533-0968 PART# OMP-2200M1



Anesthesia Hardened Case (ARMY Case is Gray) NSN 6515-01-533-1279 PART# O-A104



Anesthesia Unit with Hardened Case



Lid of Anesthesia Case with Components



Nomenclature of Components for the Lid of Anesthesia



Air Compressor Case NSN 4310-01-532-9887 PART# O-A102



Air Compressor NSN 4310-01-532-9886 PART# O-A101

MAGELLAN PHYSICAL AND ENVIRONMENTAL SPECIFICATIONS

Dimensions	Height	23 inches	12.5"
	Width	17 inches	7.25"
	Depth	23 inches	16"
	Cube	5.20 cu ft	
Weight Anesthesia system	Free Standing	55 lbs case only	100 lbs Machine with
			accessories
Weight Air Compressor/w case	Free Standing	36 lbs	
Operating Temperature Range		35° F to +160° F	
Relative Humidity (in use)		30 to 90%, non	
		condensing	
Relative Humidity (storage)		40 to 90%, non	
		condensing	
Air Compressor		120 volts, 60 Hz,	
Power Requirements		5 amps	
Watts		600 watts	

MAGELLAN ANESTHESIA SYSTEM CONSUMABLE AND ACCESSORIES (START-UP)

NSN	NOTES	Nomenclature	PN	QTY	UI	Unit Price	Total Price	MFG	Shelf Life, months	Refr ig Y/N	CONUS Ship Time, weeks
6515015333323	Included W/NSN	Annual Maintenance kit	O-A108	1	EA	\$600	\$600	Oceanic Medical	Indef	N/A	2
6515015331279	Included W/NSN	Anesthesia Apparatus Case	O-A104	1	EΑ	\$2000	\$2000	Oceanic Medical	Indef	N/A	2
6515015331216	Included W/NSN	Reusable Bundle	O-A109	1	EΑ	\$1200	\$1200	Oceanic Medical	Indef	N/A	2
6505014437083	IN THE UA Order Prior to Deployment IN THE UA	SEVOFLURANE LIQUID USP 100ML 6s	NDC0007 4-4456-04	3	PG	\$319.05	\$957.15	Oceanic Medical	24 months	N/A	2
6505015331104	Does not come with	Sevoflurane Vaporizer	O-25.1/S	1	EA	\$2,200.00	\$2,200.00		Indef	N/A	2
6530015331169	Included W/NSN	Isoflurane Vaporizer	O-25.1/1	1	EA	\$2,200.00	\$2,200.00	Oceanic Medical	Indef	N/A	2
7610015375157	Included W/NSN	CD, Operator/ Service Manual	25	1	EA	\$75	\$75	Oceanic Medical	Indef	N/A	2
6515015331177	Included W/NSN	Oxygen Analyzer	O-A105	1	EA	\$610	\$610	Oceanic Medical	Indef	N/A	2
6515015331174	Included W/NSN	Replacement Sensor for O ² Analyzer	O-105A	1	EA	\$150	\$150	Oceanic Medical	Indef	N/A	2
6530015331102	Included W/NSN	Water Trap	O-A103	1	EΑ	\$100	\$100	Medical Oceanic	Indef	N/A	2
6515015330980	Included W/NSN	PEEP Valve	O-A110	1	EΑ	\$120	\$120	Medical	Indef	N/A	2
See Resupply	Included W/NSN	9 Volt Battery		1	EΑ				Indef	N/A	2
See Resupply	Included W/NSN	Battery AA 1.5 volts		1	EΑ			0 :	Indef	N/A	2
4310015329886	Included W/NSN	Air Compressor	O-A101	1	EA	\$1800	\$1800	Oceanic Medical	Indef	N/A	2
4310015329887	Included W/NSN	Compressor Case	O-A102	1	EA	\$500	\$500	Oceanic Medical	Indef	N/A	2
4310015329881	Included W/NSN	Air Compressor with Transport Case	O-A100	1	EA	\$2275	\$2275	Oceanic Medical	Indef	N/A	2
6505001415000	IN THE UA	SOD BICARB USP 1LB	NDC0039 5-2685-01	1	CO	\$2.88	\$2.88	Cardinal Health	Indef	N/A	2
6505013628311	IN THE UA	Soda Lime NF 2.5 lbs Cartridge, 12s	Sodasorb pre pak	6	PG	\$59.12	\$59.12	Grace WR and Co.	24 mo	N/A	2

MAGELLAN ANESTHESIA SYSTEM CONSUMABLE (RESUPPLY)

NSN	Nomenclature	PN	QTY	UI	Unit Price	Total Price	MFG	Shelf Life, month	Refrig Y/N	CONUS Ship Time, weeks
6505014437083	IN THE UA ONLY SEVOFLURANE LIQUID USP 100ML 6s	NDC0007 4-4456-04		PG	\$319.05	\$319.05	Oceanic Medical	24 mo	N/A	2
6515015331174	Replacement Sensor for O ² Analyzer	O-105A	1	EA	\$150	\$150	Oceanic Medical	Indef	N/A	2
6530015331102	Water Trap	O-A103	1	EA	\$100	\$100	Oceanic Medical	Indef	N/A	2
6135009002139	9 Volt Battery	MN1604	1	PG	\$10.70	\$10.70	Duracell Inc.	Indef	N/A	2
6135009857845	Battery AA 1.5 volts	C18.1	1	PG	\$4.78	\$4.78	American NationaStd	Indef	N/A	2
6505001415000	SOD BICARB USP 1LB	NDC0039 5-2685-01	1	CO	\$2.88	\$2.88	Cardinal Health	Indef	N/A	2
6505013628311	Soda Lime NF 2.5 lbs Cartridge, 12s	Sodasorb pre pak	6	PG	\$59.12	\$59.12	Grace WR and Co.	24 mo	N/A	2
6515015331216	Reusable Bundle	O-A109	1	EA	\$1200	\$1200	Oceanic Medical	Indef	N/A	2

The Reusable Product Bundle Contains:

Mask-Size 0
Mask-Size 1, Quantity 1
Mask-Size 2, Quantity 1
Silicone Face Mask-Size 3, Quantity 1
Silicone Face Mask-Size 4, Quantity 1
Silicone Face Mask-Size 5, Quantity 1
Mask Hook Rings, Quantity 2
72" Silicone Respiration Tubing/16mm, Quantity 2
1.0L Silicone Breathing Bag, Quantity 1

12" Silicone Respiration Tubing/ 16mm, Quantity 1 KAB Absorber (without APL Valve), Quantity 1 Head Strap-Latex Free, Quantity 1 12" Reusable Tubing, Quantity 3 30mm x 19mm Connector, Quantity 1 3.0L Silicone Breathing Bag, Quantity 2 Right Angle Elbow (w/female luer lock), Quantity 1 Ported Y-Connector, Quantity 1 22mm T-Connector, Quantity 1

Special Note:

The SG's consultant for Nurse Anesthetists, has stated that he envisions One Reusable Bundle to accompany each anesthesia machine, and that for deployment, the logistician should assume that one of the disposable kits will be used with each surgery patient. Therefore, the logistician should plan for around 10 surgical procedures per machine per day.

CONCENTRATOR OXYGEN 1-5 LPM TOC

AIRSEP NEWLIFE ELITE MODEL # ELITE AS5002

Manufacturers' PHONE: (716) 691-0202 FAX: (716) 691-0174 Website: http://www.portablenebs.com/concentrator.htm

AAC "W" ITEM NSN 6515-01-383-1052 AAC "J" ITEM NSN 6515-01-434-4629

UA's: 3267,4901, 4905, 9303

USAMMA POC: Materiel Acquisition Directorate, 301-619-7403, DSN 343-7403

UNIT PRICE: \$926.08

System Description: Produces from 1 to 3 liters per minute of therapeutic oxygen, purity levels of up to 92%, 4 LPM AT 89 %, and 5 LPM AT 82 %. This system has built-in alarms for power failure and high/low pressure. Includes filters to remove dust, bacteria and other particulates, provides for the attachment of an in-line humidifier to humidify. The gas mixture delivered to the patient for use in producing oxygen rich gas mixture by drawing in room air and extracting the oxygen. Large, easy-to-read flow meter with back-lines for accurate flow settings. Built-in handles make it easy to move or lift. Large casters glide easily over virtually any flooring surface.



AIRSEP OXYGEN CONCENTRATOR CHARACTERISTICS

Dimensions	Height, in.	27.5
	Width, in.	16.7
	Depth, in.	14.5
Weight, lbs.	54	
Cube	3.85 cu ft	
Operating		
Temperature Range	40° to 105 ° F	
Relative Humidity		
(storage)	4° to 140° F	
Relative Humidity (in		
use)	0 to 95%	
Alarms	Power failure	
	High and low pressure	
	Temperature	
	Battery test	
	Low purity (Oxygen monitor with optional	
	EcoCheck)	
Performance:		
	92% at 1-3 LPM	
	89% at 1-4 LPM	
	82% at 1-5 LPM	
Power Consumption	480 Watts	
Power Requirements	120 VAC, 60 Hz, 4 amps	

AIRSEP OXYGEN CONCENTRATOR CONSUMABLES(START-UP)

NSN	Notes	Nomenclature	PN	Q T Y	UI	Unit Price	Total Price	MFG	Shelf Life, month s	Refrig Y/N	CONU S Ship Time, weeks
6515011535584	Included W/NSN	Mask, oro-nasal, child	1042	1	50 PG	\$100.23		Medline Industries	Indef	N	2
6515013656206	Included W/NSN	Mask, oro-nasal, pediatric	1011	1	50 PG	\$109.72	\$109.7	Elite Medical Products	Indef	N	2
6515011405343	Included W/NSN	Mask, rebreathing, adult	1009	1	50 PG	\$93.25		Metropolitan Medical	Indef	N	2
6515014580522	Included W/NSN	Nasal Cannula, Oxygen, 84inch non-flared	1103	1	50 PG	\$28.50		Hudson Oxygen Therapy Sales	Indef	N	2
6515014724663		Filter Bacteria			EA	\$4.20		Airsep Corp	Indef	N	2
7610015379355	Included W/NSN	Operating/Service Manual	MN105- 1			\$11.00	\$11.00	Airsep Corp	Indef	N	2

AIRSEP OXYGEN CONCENTRATOR CONSUMABLES(RESUPPLY)

NSN	Nomenclature	PN	Q T Y	UI	Unit Price	Total Price	MFG	Shelf Life, month s	Refrig Y/N	CONUS Ship Time, weeks
6515011535584	Mask, oro-nasal, child	1042	1	50 PG	\$100.23		Medline Industries	Indef	N	2
6515013656206	Mask, oro-nasal, pediatric	1011	1	50 PG	\$109.72		Elite Medical Products	Indef	N	2
6515011405343	Mask, rebreathing, adult	1009	1	50 PG	\$93.25		Metropolitan Medical	Indef	N	2
6515014580522	Nasal Cannula, Oxygen, 84inch non-flared	1103	1	50 PG	\$28.50		Hudson Oxygen Therapy Sales	Indef	N	2
6515014724663	Filter Bacteria	F1001-1	1	EA	\$4.20		Airsep Corp	Indef	N	2

LIGHT HEAD GENERAL PURPOSE HEADBAND TOC

WELCH ALLYN INCORPORATED MODEL # 49020

Manufacturer's Phone: (315) 685-4560 FAX: (315) 683-3361

Website: http://www.welchallyn.com

AAC "J" ITEM NSN 6230-01-520-3474

UA's: 3267, 4901, 4905, 5267, N320, N301, N308, N309, N314, 4714, F301, F308, F309

USAMMA POC: Materiel Acquisition Directorate, 301-619-7403, DSN 343-7403 UNIT PRICE: \$447.53

Special Features:

- Weighting less than four ounces, it's one of the most comfortable lightweight headlights available
- With a color temperature of 5500 Kelvin, this light supplies bright, white, shadow-free light allowing the end user to see tissue characteristics without distortion
- It's operating life expectancy is 10,000
- Enjoy the flexibility of operating the headlight using the direct power source or the rechargeable "belt-clip: portable power source.

Clinical Benefits

- Long operating life (10,000 hours of continuous burn)
- More energy efficient than incandescent and halogen lamps
- Cool beam is safe to touch
- Instant light (less than 100ns)
- Virtually maintenance-free operation
- No UV rays

Suggested Applications The Solid State Procedure Headlight provides ideal illumination for procedures such as minor surgery, general examinations, foreign body removal, OB/GYN applications and procedures, dermatology examinations or any procedure that requires a small, homogenous and well-defined spot.

WELCH ALLYN.

SURGICAL HEADLIGHT



Technical Specifications

Spot Size Range: 1.5 to 6 inches at the working distance **Light Source**: Five-watt Solid State lamp, color temperature 5500 Kelvin, TBD Lumens, life 10,000 hours continuous burn

Working Distance: 16 inches

Battery Run-Time: One hour continuous run-time on a fully charged battery

Battery Life: Approximately 2.5 years (depending on usage)

Warranty: One-year limited warranty

CONSUMABLES ACCESSORIES (STARTUP)

NSN	NOTES	Nomenclature	PN	QT Y	UI	Unit Price	Total Price	MFG	CONUS Ship Time, weeks
6530015225307	Included W/NSN	Carrying Case	49099	1	EA	\$193.98	\$193.98	WELCH ALLYN	2
6230015221304	Included W/NSN	Charger Only for Portable Power Source	74180	1	EA	\$37.11	\$37.11	WELCH ALLYN	2
6230015221307	Included W/NSN	Portable Power Source Only	75200	1	EA	\$154.78.	\$154.78	WELCH ALLYN	2
6230015221337	Included W/NSN	Direct Power Supply	75270	1	EA	\$50.75	\$50.75	WELCH ALLYN	2



CARRYING CASE, PART# 49099 6530015225307



PORTABLE POWER SOURCE ONLY, PART # 75200 6230015221307



DIRECT PLUG IN TRANSFORMER UNIT, PART # 75270 6230015221337



CHARGER, PART # 74180 6230015221304

LIGHT SURGICAL STAND COLOR CORRECT SHADOW TOC

FEDMEDICAL INC MODEL # FMI-301FB

Manufacturer's PHONE: (843) 554-7004 FAX: (843) 832-4343

Website: http://www.fedmedical.com

AAC "J" ITEM NSN 6530-01-518-9854

UA's: 2267, 4901, 4905, N308, N309

USAMMA POC: Materiel Acquisition Directorate, 301-619-7403, DSN 343-7403 UNIT PRICE: \$6,187.16

System Description: Color-correct, shadow-free, illumination, full-sized surgical light, floor mounted, swivel light, 12V halogen bulb, 50 watt, lamp housing diameter, 11.4 inch, 6 hour back-up battery and case, for field or theater of operation use, ultra-light suspension. The base of this light is made of 14 gauge, powder coated steel and can hold 250 lbs. The lamp suspension allows fingertip control and secure, drift-free positioning.

Special Features:

Internal "smart" circuit automatically adjusts for 110-220VAC or 24VDC 62 amp hr 50,000 lux of color-correct brilliance at (1-m)

More accurate tissue differentiation and diagnosis—with 4,500 K color temperature for truer colors

27" depth of field and 5.5" field diameter Optimized shadow reduction Sealed light head keeps contaminates out Quick, tool-free bulb exchange Extremely low heat emission Drift-free suspension



CHARACTERISTICS

Dimensions Case	Height	20"	Maximum from lens to floor 78" (198 cm)
	Width.	28"	
	Depth	34"	
Weight		120 lbs	
Cube Ft		11.01	
Operating Temperature			
		35°F to 130°F	
Operating Humidity		90 RH	
Storage Temperature		32°F to 150°F	
Storage Humidity		99 RH	
Power Requirements		110-220 VAC	24 VDC
Amps		55 amps	2 amps
Watts		230 watts	



BASE OF SYSTEM



16

LIGHT SURGICAL FIELD UNIT ACCESSORIES (START-UP)

NSN	NOTES	Nomenclature	PN	QTY	UI	Unit Price	Total Price	MFG	Shelf Life, months	Refrig Y/N	CONUS Ship Time, weeks
6530015275566	Included W\NSN	Reusable,sterilizable light handle cover	41-2001	1	EA	\$89.25	\$89.25	Fedmedical inc.	N	N	2
6530015275501	Included W\NSN	Disposable light handle cover	41-2002	1	BX\25s	\$85.45	\$85.45	Fedmedical inc.	N	N	2
6530015275497	Included W\NSN	Bulb, 12 volt, 50 watt, Halogen	41-2010	1	EA	\$87.35	\$87.35	Fedmedical inc.	N	N	2
6530015275487	Included W\NSN	15 ft DC cord w/connector	41-2020	1	EA	\$60.75	\$60.75	Fedmedical inc.	N	N	2
6530015275490	Included W\NSN	Hardened case with foam	41-2100	1	EA	\$844.65	\$844.65	Fedmedical inc.	N	N	2
6130015263300	Included W\NSN	12 VOLT Battery, 55 amp hour	41-1002	1	EA	\$100.00	\$100.00	Fedmedical inc.	N	N	2

LIGHT SURGICAL FIELD UNIT ACCESSORIES (RESUPPLY)

NSN	Nomenclature	PN	QTY	UI	Unit Price	Total Price	MFG	Shelf Life, months	Refrig Y/N	CONUS Ship Time, weeks
6530015275566	Reusable,sterilizable light handle cover	41-2001	1	EA	\$89.25	\$89.25	Fedmedical inc.	N	N	2
6530015275501	Disposable light handle cover	41-2002	1	BX\25s	\$85.45	\$85.45	Fedmedical inc.	N	N	2
6530015275497	Bulb, 12 volt, 50 watt, Halogen	41-2010	1	EA	\$87.35	\$87.35	Fedmedical inc.	N	N	2
6530015275487	15 ft DC cord w/connector	41-2020	1	EA	\$60.75	\$60.75	Fedmedical inc.	N	N	2
6130015263300	12 VOLT Battery, 55 amp hour	41-1002	1	EA	\$100.00	\$100.00	Fedmedical inc.	N	N	2

OTOSCOPE & OPHTHALMOSCOPE SET TOC

WELCH ALLYN MODEL 92821

Manufacturer's PHONE: (503) 530-7500 FAX: (503) 526-4919

Website: http://www.welchallyn.com


AAC "J" ITEM NSN 6515-01-333-3165

UA's: 2256, 2264, 2265, 3264, 9103, 9110, 9111, M308, M309, 4901

USAMMA POC: Materiel Acquisition Directorate, 301-619-7403, DSN 343-7403 UNIT PRICE: \$230.58

Features:

- 2.5V Pocket Scope Ophthalmoscope uses halogen bulbs for true tissue color and consistent, long lasting illumination. It has 6 aperture selections for general and specialist use, and 48 lenses for better resolution.
 - 2.5V Otoscope also has built-in throat illuminator two-in-one instrument features halogen illumination and fiberoptics for a cool light with no reflections or obstructions, plus a rectangular viewing lens for instrumentation under magnification.
 - 2.5V Pocket Scope handle has a smooth rheostat to control light intensity and features a handy pocket clip.



ACCESSORIES PACKAGE (START-UP)

NSN	NOTES	Nomenclature	QTY	UI	PART#	Unit Price	Total Price	MFG	Shelf Life, month s	Refrig Y/N	CONU S Ship Time, weeks
	INCLUDED WITH NSN	BULB REPLACEMENT EXAM INSTRUMENT F/HALOGEN OTOSCOPE									
6515015205740		2.5V	1	EA	03400-U	\$12.60	\$12.60	WELCH/ALLYN	indef	N	2
6515015205754	INCLUDED WITH NSN	BULB REPLACEMENT EXAM INSTRUMENT F/OPHTHALMOSCOPE	1	EA	03900-U	\$13.21	\$13.21	WELCH/ALLYN	indef	N	2
6515015205763	INCLUDED WITH	HEAD OPHTHALMOSCOPE POCKET 2.5V HALOGEN BULB RED FREE FILTER MICRO/SM	1	EA	13000	\$88.27	\$88.27	WELCH/ALLYN	indef	N	2
		HEAD OTOSCOPE DIAGNOSTIC HALOGEN	_			φου. 2 /	7 0 0 0 0				
6515015205725	INCLUDED WITH NSN	HPX 2.5V 9.8 DIOPTER 4IN FOCAL LENGTH	1	EA	21111	\$59.79	\$59.79	WELCH/ALLYN	indef	N	2
6515015205778	INCLUDED WITH NSN	2.5 VOLT HANDLE (ACCEPTS TWO AA BATTERIES)	1		72830		\$81.13	WELCH/ALLYN		N	2
6545015190982	INCLUDED WITH NSN	CASE SOFT ZIPPER F/POCKETSCOPE	1	EA	05928-U	\$12.00	\$12.00	WELCH/ALLYN	indef	N	2

CONSUMABLES/ OPTIONAL (RESUPPLY)

NSN	Notes	Nomenclature	QTY	UI	PART#	Unit Price	Total Price	MFG	Shelf Life, month s	Refrig Y/N	CONU S Ship Time, weeks
		BATTERY						AMERICAN			
		NONRECHARGEABLE			20-0571-			NATIONAL			
6135009857845		ALKALINE 1.5V 1 YEAR SHELF LIFE 24S, AA CELL	1	PG	1988 NEDA 15A	\$4.78	\$4.78	STANDARDS INST	indef	N	2
0133007037043		DISPOSABLE SPECULA	-		31237-	φ4.70	φ4.70	CARDINAL	macı	11	
6515015250236		4.25MM, 800 COUNT/BAG	1		010A	\$29.04	\$29.04	HEALTH	indef	N	2
		DISPOSABLE SPECULA			31237-			CARDINAL			
6515015250240		2.75MM, 800 COUNT/BAG	1	BX	020A	\$29.04	\$29.04	HEALTH	indef	N	2
6515013294847	IN THE UA	SPECULUM OTOSCOPE SLIT TYPE 4MM SIZE ADULT PLAS 1000S	1	PG	52434	\$19.25	\$19.25	WELCH/ALLYN	Indef	N	2
6515015205740		BULB REPLACEMENT EXAM INSTRUMENT F/HALOGEN OTOSCOPE 2.5V	1	EA	03400-U	\$12.60	\$12.60	WELCH/ALLYN	indef	N	2
6515015205754		BULB REPLACEMENT EXAM INSTRUMENT F/OPHTHALMOSCOPE	1	EA	03900-U	\$13.21	\$13.21	WELCH/ALLYN	indef	N	2

ACCESSORIES PACKAGE RESUPPLY

NSN	Nomenclature	QTY	UI	PART#	Unit Price	Total Price	MFG	Shelf Life, month s	Refrig Y/N	CONU S Ship Time, weeks
6515015205740	BULB REPLACEMENT EXAM INSTRUMENT F/HALOGEN OTOSCOPE 2.5V	1	EA	03400-U	\$12.60	\$12.60	WELCH/ALLYN	indef	N	2
6515015205754	BULB REPLACEMENT EXAM INSTRUMENT F/OPHTHALMOSCOPE	1	EA	03900-U	\$13.21	\$13.21	WELCH/ALLYN	indef	N	2
6515015205763	HEAD OPHTHALMOSCOPE POCKET 2.5V HALOGEN BULB RED FREE FILTER MICRO/SM	1	EA	13000	\$88.27	\$88.27	WELCH/ALLYN	indef	N	2
6515015205725	HEAD OTOSCOPE DIAGNOSTIC HALOGEN HPX 2.5V 9.8 DIOPTER 4IN FOCAL LENGTH	1	EA	21111	\$59.79	\$59.79	WELCH/ALLYN	indef	N	2
6515015205778	2.5 VOLT HANDLE (ACCEPTS TWO AA BATTERIES)	1	EA	72830	\$81.13	\$81.13	WELCH/ALLYN	indef	N	2

REFRIGERATOR BLOOD COOLING& STORAGE FIELD ENVIRONMENT TOC

DOUBLEDAY ACUISITIONS LLC ACUTEMP MODEL # HMC-MIL-1

Manufacturer's PHONE: (937) 312-0114 FAX: (937) 312-1277 Website: http://www.estglobal.com/hemacool_military.html

AAC "W" ITEM NSN 4110-01-497-9564 AAC "J" ITEM NSN 4110-01-506-0895

UA's: 213A, 3263, 3267, 901A, 504A, N302, N504, N703, N503, N304, N303, N704, F303, F306

USAMMA POC: Materiel Acquisition Directorate, 301-619-7403, DSN 343-7403 UNIT PRICE: \$5,560.00


Description: The HemaCoolTM employs new technology to protect critical blood supplies under field conditions. It is ergonomically designed for operations in adverse environments, incorporating features and controls to precisely maintain the required temperature for blood storage.

Features:

- Precise temperature control under adverse conditions
- Easily transportable
- Can run on a variety of power sources including AC, DC, onboard batteries, and solar array
- Rugged design for demanding applications
- Available with Sled Rails, Wheels, or Skis

HEMACOOL REFRIGERATION SYSTEM











HEMACOOL REFRIGERATION SYSTEM PHYSICAL AND ENVIRONMENTAL SPECIFICATIONS

Dimensions	Height	21.8 inches
	Width	21 inches
	Length	37.5 inches
Payload Dimensions	Height	13 inches
Payload Volume	Width	14 inches
	Length	18 inches
Payload Volume		2 cu ft (56.6 liters)
Empty Weight,		145 lbs
Cube		9.5 cu ft
Storage Only		40 x 450 ml or 60 x 250 ml units
Operating Temperature		-4°F min., 120°F max. (-20°C to 49°C)
Storage Temperature		-22°F min., 149°F max. (-30°C to 65°C)
Temperature Limits		-4°F min., 120°F max. (-20°C to 49°C)
Battery Set (2 Each)		12/24 VDC Internal 40 amp-hour Battery Set
Power Requirements		100/240 Volts AC, 46/63 Hz
amps		.55 amps
Watts		55 watts







HEMACOOL, BLOOD BAG BASKET PART # 100000



HEMACOOL SHOWN WITH PLASMA Part # HMC-MIL-1



HEMACOOL CONTROL PANEL



HEMACOOL SHOWN WITH VACCINE Part # HMC-MIL-1

HEMACOOL REFRIGERATION SYSTEM ACCESSORIES AND CONSUMABLES (START-UP)

NSN	NOTES	Nomenclature	PN	QTY	UI	Unit Price	Total Price	MFG	Shelf Life, months	Refrig Y/N	CONU S Ship Time, weeks
6515015130792	INCLUDED W/NSN	Blood Basket	100,000	5	EA	\$16.44	\$82.20	ACUTEMP	N/A	N	2
4110015188542	INCLUDED W/NSN	AC Power Cord	VXC-1-06	1	EA	\$16.00	\$16.00	ACUTEMP	N/A	N	2
6150015121007	INCLUDED W/NSN	DC Power Cord	100003	1	EA	\$87.00	\$87.00	ACUTEMP	N/A	N	2
4110015188252	INCLUDED W/NSN	Battery	101880	2	SE	\$60.00	\$120.00	ACUTEMP	N/A	N	2

HEMACOOL REFRIGERATION SYSTEM CONSUMABLE (RESUPPLY)

NSN	Nomenclature	PN	QTY	UI	Unit Price	Total Price	MFG	Shelf Life, months		CONU S Ship Time, weeks
4110015188252	Battery	101880	2	SE	\$60.00	\$120.00	ACUTEMP	N/A	N	2

COMPANY IS OUT OF BUSINESS ITEMS ARE STILL IN STOCK

SINK UNIT SURGICAL SCRUB TOC

RAN-PAIGE CO INC MODEL 0200-96-C-8509

AAC "W" ITEM NSN 6530-01-431-9005 AAC "J" ITEM NSN 6530-01-429-6715

UA's: M301, M308, M309, 4901

USAMMA POC: Materiel Acquisition Directorate, 301-619-7403, DSN 343-7403

UNIT PRICE: \$946.74

Special Features: Portable and light weight. Consists of a hollow tubular frame support, a plastic polypropylene basin, a pump and a heater, a foot pedal and associated tubing and electrical components. Electrical and water are activated by the foot pedal. The water heater is an encapsulated inline type 1200 to 1300 Watts. The maximum water temperature is 125 degrees. This includes a reusable container.



CHARACTERISTICS

Dimensions	Height	N/A
	Width	N/A
	Depth	N/A
Weight	59 lbs	
Cubic ft	6.16	
Power Requirements	115/230 VAC, 50/60 Hz	
_	1300 Watts	

STERILIZER SURGICAL INSTRUMENT STEAM TOC

THIS SYSTEM IS PURCHASED FROM GOVERNMENT SCIENTIFIC SYSTEMS INC. Supplier's Phone: (703) 734-1805 FAX (703) 734-1803

MANUFACTURED BY TUTTNAUER USA CO. **MODEL # 2540M**

Manufacturer's Phone: (631) 737-4850 FAX: (631) 737-0720

Website: http://www.govsci.com http://www.tuttnauer.com

AAC "J" ITEM NSN 6530-01-531-4807


UA's: M302, M403, 4901, 4905, 4912

USAMMA POC: Materiel Acquisition Directorate, 301-619-7403, DSN 343-7403

UNIT PRICE: \$3,611.54

Systems Description: Tuttnauer manual autoclaves set the standard for steam Sterilization. The Tuttnauer manual autoclave is designed to compliment any healthcare and laboratory facility. Our basic manual autoclave will satisfy all of your sterilization needs. Time tested reliability and durability are built into every Tuttnauer product. The Tuttnauer M Series is also available in a quick cycle model. This sterilizer offers all the proven, dependable features of our manual autoclave, with the added benefit of reducing the total sterilization cycle time by 50%. Speed and reliability are accomplished without sacrificing load size. This is the perfect choice for quick instrument turn-around or a high-volume office.

Special Features: A fast Cycle Time .9 minutes from a hot start *(Standard Unwrapped Cycle time). Automatic shut off at the end of both the sterilization and dry cycles. A long life electro polished chamber and door. It has a double safety locking device that prevents the door from opening while chamber is pressurized. The drain valve is located on the front, allowing for a quick and easy draining of water reservoir. It has a dual safety thermostat to protect against overheating. This sterilizer is a table top steam autoclave; sterilization cycle and separate drying cycle feature automatic shut off. The size of the chamber is 10 inches by 18 inches deep






Hardened Case for the Tuttnauer Sterilizer



Sterilizer shown in Hardened Case



Instrument Pouch Rack

Characteristics

Overall Dimensions		
	Height	14"
	Width	20"
	Depth	20"
Operating temp	59° to 95 ° F	
Storage temp	59° to 95° F	
Relative humidity	0 to 85%	
Chamber Dimensions		10" diameter x18"
		deep"
Weight	50 lbs	
Cube	19.55 cu ft	
Power Supply	120 voltage nominal 12 amp VAC 50/60 Hz	
Watts	1400 W	

STERILIZER SURGICAL DRESSING CONSUMABLES (START-UP)

NSN	NOTES	Nomenclature	PN	QTY	UI	Unit Price	Total Price	MFG	Shelf Life, months	Refrig Y/N	CONUS Ship Time, weeks
6530015408014	Included W/NSN	Pouch Rack	AR910	1	EA	\$43.79	\$43.79	GSS INC	Indef	N/A	2
6530015408023	Included W/NSN	Tray	CT620010	4	EA	\$65.55	\$65.55	GSS INC	Indef	N/A	2
6530015392908	Included W/NSN	Case, Hardened	HDD041805200	1	EA	\$851.65	\$851.65	GSS INC	Indef	N/A	2
7610015408195	Included W/NSN	Manual, Operato/Service	ЕМНС01.	1	EA	\$1.00	\$1.00	GSS INC	Indef	N/A	2

ULTRASOUND, PORTABLE 180 SONOSITE SYSTEM TOC

SONOSITE, INC MODEL 180Plus

Manufacturer's PHONE: (425) 951-1243 FAX (801) 751-1135

Website: http://www.sonosite.com/content/view/37/185/

AAC "W" ITEM NSN 6525-01-507-0073 AAC "J" ITEM NSN 6525-01-503-7182

UA's: 2267, 4901, 4905, 5267

USAMMA POC: Materiel Acquisition Directorate, 301-619-7403, DSN 343-7403 PRICE: 36,462.98

System Description: Lightweight portable diagnostic ultrasound device used to assist in the detection of Rapid triage and assessment of trauma (FAST), visualization of abdominal fluid collection, evaluation of pericardial or pleural effusions and tamponade, immediate assessment of pelvic pain and abnormal uterine bleeding, rapid evaluation of acute abdominal pain (kidney, cholelithiasis), and easy emergency obstetric exams (IUP, fetal viability)

Operator Familiarization: CD-ROM is available.

CLINICAL APPLICATIONS

Abdominal

Vascular

Breast

Obstetrical

Pediatric/Neonatal

Intraoperative Procedures

Interventional Procedures

Cardiac

Prostate

Small Parts

Gynecological


Musculoskeletal



ULTRASOUND PHYSICAL AND ENVIRONMENTAL SPECIFICATION

Dimensions	Height	13.3 inches
	Width	7.6 inches
	Depth	2.5 inches
	Cube	0.14cuft
Weight		5.4 lbs
Power Requirements		12 VDC or 120 VAC
Battery Life		1.5hrs – 4.0hrs fully charged
Battery characteristics		Lithium Ion






MENU SELECT CONTROLS FIGURE 1




NEAR/FAR/GAIN AJUSTORS FIGURE 2




MENU, DEPTH AND ZOOM FIGURE 3



TRACKBALL FIGURE 4




PATIENT BUTTON FIGURE 5



ARROW AND FREEZE KEYS FIGURE 6



LCD CONTROLS FIGURE 7



Number	Feature	Number	Feature
1	power switch, located on the rear of the system handle	10	battery charge indicators
2	near, affects gain of shallow echoes	11	LCD (liquid crystal display) brightness control
3	far, affects gain of deeper echoes	12	LCD contrast control
4	gain, affects overall gain	13	LCD
5	menu select controls	14	Print/VCR or Print key
6	Menu, Depth, and Zoom	15	Cine Arrow keys and Freeze key
7	trackball	16	mode controls
8	Patient	17	battery release
9	Function key		
	•		

ULTRASOUND CONSUMABLES AND ACCESSORIES

Package Order for FST and Vet Sets only

Hand-Carried Ultrasound Systems:		PART NO.	PRICE	QTY
Transducers (C1 products):	NOTE: Transducers on this price list have the current version software and the existing customer system may require an update to ensure transducer compatibility.			
SonoSite 180 PLUS & ELITE Fourth Generation (1.99)	Portable ultrasound system includes: display module, 2D Grayscale, color power Doppler (CPD) and directional color power Doppler (DCPD) capability, M-mode, PC Direct connectivity capability (w/ SiteLink & PC Direct Serial Cable ordered separately). Also includes battery, universal AC power supply, external video and printer cables, ultrasound gel, and user guides.			
	180PLUS Does not support Continuous Wave (CW) Doppler.	L02464	\$8036.00	1
C15 e / 4–2, micro- curved array transducer	15–mm, broadband (4 - 2 MHz) micro-curved array for thoracic and abdominal applications. Provides 2D Grayscale, CPD or DCPD (depending on exam type), CW, PW, M-mode, and ERH. 5.5 ft (1.7m) cable and pinless connector. Not compatible with non-1.99 systems.	P02461	\$8610.00	1
C60 / 5–2, curved array transducer	60-mm, broadband (5 - 2 MHz) curved array for abdominal, obstetric, and gynecologic applications. Provides 2D Grayscale, CPD, DCPD, PW, M-mode, and THI. 5 ft (1.5 m) cable and pinless connector. Compatible with biopsy guide part number P01882. Some early first generation SonoSite systems (1.5X with ARM < 02.80.006.014) require system software upgrade module (no charge) to ensure compatibility. Contact SonoSite Customer Support prior to ordering for additional details.	P02115	\$4510.00	1
L38 / 10-5, linear array transducer	38-mm, broadband (10 - 5MHz) linear array for breast, small parts, vascular, and musculoskeletal applications. Provides 2D Grayscale, CPD, PW, and M-mode. 5.5 ft. (1.7 m) cable and pinless connector. Compatible with biopsy guide part number P01300. Not compatible with 1 st generation systems.	P04101	\$8610.00	1

ICT / 7–4, intracavitary array transducer	11-mm, broadband (7 - 4 MHz) intracavitary array for gynecologic, obstetric and urologic applications. Provides 2D Grayscale, CPD, PW, and M-mode. 5 ft (1.5m) cable and pinless connector. Compatible with biopsy guide part number P01869. Not compatible with 1 st generation systems.	P02450	\$4510.00	1
Battery – PLUS/ELITE	11.1 volt, 3.0 amp-hour rechargeable lithium-ion battery.	P00049	\$324	1
SiteCharge® dual battery charger	Desktop charger used to recharge two system batteries at a time. Recommended for heavy battery use environments.	L00552	\$492	
Sonosite Military Hard Case		P03808	\$656.00	

180 PLUS RESUPPLY CONSUMABLES

NSN	Nomenclature	PN	QTY	UI	Unit Price	Total Price	MFG	Shelf Life, mont hs	Refrig Y/N	CONUS Ship Time, weeks
6515015046163	Latex Probe Cover	610- 214	1	50/ PG	\$156.00		Civco Medical Instruments	N	N	2
6515012317249	Transmission Gel Ultrasound0.25 liter	01-08	1	12s/PG	\$31.84	\$31.84	Parker Labs Inc.	N	N	2

3.5 x 20cm Latex Covers

These latex transducer covers are individually packaged with colored elastic bands in easy-to-open perforated bags. Conveniently packaged in a compact box, the covers offer an effective means to protect equipment, patients and professionals from the risks of cross-contamination.

Ref.#	Product Description	Qty.
610-214	Sterile 3.5 \times 20cm (1.4" \times 7.9") latex cover	50
610-010	Non-sterile 3.5 \times 20cm (1.4" \times 7.9") latex cover	50



180 PLUS ACCESSORY START-UP

NSN	NOTES		PN	QTY	UI	Unit Price	Total Price	MFG	Shelf Life, months	Refrig Y/N	CONUS Ship Time, weeks
	Included W/NSN	SONOSITE 180 PLUS	P02522	1	EA	\$8036.00	\$8036.00	SONOSITE	N	N	3
6525015023728	W/NSN		P02461	1	EA	\$8610.00	\$8610.00	SONOSITE	N	N	3
6525015023739	W/NSN		P02115	1	EA	\$4510.00	\$4510.00	SONOSITE	N	N	3
6525015036742	W/NSN		P04101	1	EA	\$8610.00	\$8610.00	SONOSITE	N	N	3
6525015023739	W/NSN	i	P02450	1	EA	\$4510.00	\$4510.00	SONOSITE	N	N	3
6525014983603	Included W/NSN	Battery – PLUS/ELITE	P00049	2	EA	\$324.00	\$648.00	SONOSITE	N	N	3
6130014902678	Included W/NSN	SiteChargedual battery charger	L00552	1	EA	\$492.00	\$492.00	SONOSITE	N	N	3
		Sonosite Military Hard Case	L03808	1	EA	\$820.00	\$820.00	SONOSITE	N	N	3
		Transmission Gel Ultrasound0.25 liter	01-08	1	EA			Parker Labs Inc.	N	N	3
7610015436723		C1.99 PLUS and ELITE ultrasound system Service Manual	P02913	2	EA	\$28.70	\$57.40	SONOSITE	N	N	3
7610015437003		Sonosite Ultrasound System Users Guide	P02614	2	EA	\$28.70	\$57.40	SONOSITE	N	N	3
NO NSN	Included	Sonosite Ultrasound System Quick Reference Guide	P02813	1	EA	\$20.50	\$20.50	SONOSITE	N	N	3
		Sonosite Ultrasound System User Guide Supplement	P05020	1	EA			SONOSITE	N	N	3
	Included W/NSN	Sonosite Imaging Accessory Manual		1	EA			SONOSITE	N	N	3
	Included W/NSN	Medical Ultrasound Safety Manual	P00809	1	EA			SONOSITE	N	N	3
	Included W/NSN	Power Cord	P00848	2	EA	\$16.40	\$32.80	SONOSITE	N	N	3
		Power Supply, 85-264 VAC, 50/60 Hz, 16VDC 45 Watts	L00538	2	EA	\$77.90	\$155.80	SONOSITE	N	N	3
NO NSN Required	Included W/NSN	Cable Printer, Control	P00537	1	EA	\$24.60	\$24.60	SONOSITE	N	N	3
NO NSN Required	Included W/NSN	Cable, RCA/BNC, Video	P00536	1	EA	\$28.70	\$28.70	SONOSITE	N	N	3
6515015084541	Included W/NSN	Cable, Serial, PC Direct	P02046	1	EA	\$82.00	\$82.00	SONOSITE	N	N	3



SONOSITE, ULTRASOUND MODEL 180Plus WITH HARDENED CASE

A full line of broadband transducers

SonoSite manufactures a variety of high-quality broadband transducers. They are lightweight, ergonomically designed for optimal user comfort, rugged and feature rapid, pinless connectors.



L38/10-5 38-mm broadband linear array

Clinical Applications

- Small parts imaging: thyroid, testicular, and musculoskeletal
- Breast
- Vascular

Ultrasound guided procedures:

Line placements, biopsies, drainage procedures

Imaging Modes:

2D, M-mode, Color Power Doppler, Pulsed Wave Doppler (option)

Physical Characteristics

Frequency: broadband 10-5 MHz

Maximum Depth: 7 cm

Maximum Field of View: 38 mm

Aperture: 38 mm

Biopsy guide:

for 14-23 gauge needles with depth range from 0.7-3.4 cm

C15/4-2 15-mm broadband

array transducer

Clinical Applications

- Adult cardiac
- General-purpose abdominal
- Trauma Assessment (F.A.S.T. exam)
- General Imaging: abdominal and thoracic

Imaging Modes:

2D, M-mode, Color Power Doppler, PowerMap Directional Color Power Doppler in cardiac settings, Pulsed Wave Doppler (option), Tissue Harmonic Imaging (option)

Physical Characteristics

Frequency: broadband 4-2 MHz Maximum Depth: 24.6 cm Maximum Field of View: 101°



C60/5-2

60-mm broadband curved array

Clinical Applications

- General-purpose abdominal
- Obstetric
- Gynecologic

Imaging Modes:

2D, M-mode, Color Power Doppler, PowerMap Directional Color Power Doppler, Pulsed Wave Doppler (option), Tissue Harmonic Imaging (option)

Physical Characteristics

Frequency: broadband 5-2 MHz Maximum Depth: 22 cm Maximum Field of View: 57°

ICT/7-4 11-mm broadband intercavitary array

Clinical Applications

- Gynecologic
- Obstetric
- Urologic

Ultrasound Guided Procedures:

Tissue sample retreival

Imaging Modes:

2D, M-mode, Color Power Doppler, Pulsed Wave Doppler, Pulsed Wave Doppler (optional)

Physical Characteristics

Frequency: broadband 7-4 MHz Maximum Depth: 10.4 cm Maximum Field of View: 135°

Biopsy Guide:

for 16-18 gauge needles with depth range from 0.5-7.0 cm

